

# COMMERCIAL

TRUCK EQUIPMENT CO.

## Renn 15' HSSL Gravel Box on International HX620



### CHASSIS SPECIFICATIONS

- International NX 620 6x4
- Cummins X15 500 EPA 2017 565 HP @ 1800 RPM
- Fuller RTLO(F)-18918B manual transmission
- Front axle: Meritor MFS-16-143A wide track I-beam type, 16,000 lb. capacity
- Rear axle: Meritor RT-46-164EH single reduction, standard width, 46,000 lb. capacity with driver controlled locking differential in forward-rear and rear-rear
- Front tires: Goodyear 385/65R22.5 G296 MSA , 488 rev/mile, load rating "J", 18-ply
- Rear tires: Goodyear 11R24.5 Unisteel G296 G177, 471 rev/mile, load rating "H", 18-ply
- Paint: Winter White

### EQUIPMENT SPECIFICATIONS

- Renn 15' high side, sloped gate gravel box
- Sides: 34" high double wall construction, 12-gauge high tensile steel inner and outer walls
- Tailgate: 46" high double wall construction, 3/16" AR200 inner and 12-gauge outer
- Floor: 3/16" AR400 one piece floor formed up each side
- Front: 46" high, 10-gauge high tensile steel
- Hi-front screen guard
- Michel's electric flip tarp kit (aluminum) with aux tarp controls to hitch
- Flip ladder and inside step
- Air actuated cab controls with custom tower
- 50-gallon upright hydraulic tank
- Commercial hitch with 2300 no-slack pintle
- Plumbed for quad



*For more information and pricing, please contact your local branch.*

**Stock Number: NV4365369**

Providing expert truck equipment solutions across Canada

[www.comtruck.ca](http://www.comtruck.ca) 1-800-665-6126

Vancouver - Surrey - Calgary - Edmonton - Regina - Winnipeg - Woodstock - Quebec